

Ref: PetEx.Spec.01

SPECIFICATION

Furnace oil – 180 (HPCL)

Sr.no	Parameters	Test Method	Units	Result Value
1.	Appearance	Visual	-	Dark
2.	Density 15°C - Top	IS 1448 P: 16	-	.9685
3.	Density 15°C - Middle	IS 1448 P: 16	-	.9689
4.	Density 15°C - Bottom	IS 1448 P: 16	-	.9709
5.	Density 15°C	IS 1448 P: 16	-	.9699
6.	Kinematic Viscosity @ 50°C	IS 1448 P: 25	cSt	Max 180/ Result - 156.1
7.	Flash Point - Pmcc	IS 1448 P: 21	°C	75
8.	Water Content	IS 1448 P: 40	% Vol	Max 1.00/Result - .30
9.	Sulphur Total	ASTM D 4294	% Mass	2.89
10.	Pour Point	IS 1448 P: 10	°C	Max 27/ Result - 0
11.	Sediment	IS 1448 P: 30	% Mass	.04

- The photocopies of following licenses are required:
GST Certificate, Explosive License for B class storage.
- The price is subject to change. Pl confirm before payment.
- Specification as provided by the manufacturer
- For sample, price, delivery, and availability Pl contact Mr. Nilesh – 9920494214,
Mr. Varun – 9004365926, Office -91 22 28077450, 91-22 28017099