

Ref: PetEx.Spec.05

## SPECIFICATION

### Furnace oil – 380 (HPCL)

| Sr.no | Parameters                 | Test Method   | Units  | Result Value       |
|-------|----------------------------|---------------|--------|--------------------|
| 1.    | Appearance                 | Visual        | -      | Dark               |
| 2.    | Density 15°C               | IS 1448 P: 16 | -      | 0.9673             |
| 3.    | Kinematic Viscosity @ 50°C | ISO 3104      | cSt    | 380 Max            |
| 4.    | Flash Point - Pmcc         | ISO 2719      | °C     | 85                 |
| 5.    | Water Content              | IS 1448 P: 40 | % Vol  | Max 0.5            |
| 6.    | Sulphur Total              | ASTM D 4294   | % Mass | 2.40 Max           |
| 7.    | Pour Point                 | IS 1448 P: 10 | °C     | Max 30/ Result - 0 |
| 8.    | Sediment                   | IS 1448 P: 30 | % Mass | .04                |
| 9.    | Gross Calorific Value      | IS 1448 P: 7  | cal/gm | 10150              |

- The photocopies of following licenses are required:  
GST Certificate, Explosive License for C class storage required for more than 44 kl storage.
- The price is subject to change. Pl confirm before payment.
- Specification as provided by the manufacturer
- For sample, price, delivery, and availability Pl contact Mr. Nilesh – 9920494214, Mr. Varun – 9004365926, Office -91 22 28077450, 91-22 28017099