

SPECIFICATIONS
“MIXED HYDROCARBON OIL (MHO)”

| Sr. No. | Parameters | Test Method | Unit | Result |
|---------|-----------------|-------------|--------|--------------|
| 1. | Appearance | | Visual | Light Yellow |
| 2. | Sulphur Content | ASTM D 2622 | % Wt. | <10 ppm |
| 3. | Density @ 15°C | ASTM D 1298 | Kg/l | 0.831 |
| 4. | Flash Point | ASTM D 93 | °C | 29.8 |
| 5. | Viscosity @40°C | ASTM D 445 | cSt | 3.5 |
| 6. | DISTILLATION | | | |
| | IBP | ASTM D 86 | °C | 76 |
| | 10% | ASTM D 86 | °C | 235 |
| | 20% | ASTM D 86 | °C | 261 |
| | 30% | ASTM D 86 | °C | 278 |
| | 40% | ASTM D 86 | °C | 291 |
| | 50% | ASTM D 86 | °C | 301 |
| | 80% | ASTM D 86 | °C | 333 |
| | 90% | ASTM D 86 | °C | 348 |
| | 95% | ASTM D 86 | °C | 362 |
| | FBP @ 98% | ASTM D 86 | °C | 373 |

1. The photocopies of following licenses are required: GST Licence, Explosive Class B storage licence.
2. The price is subject to change. Pl confirm before payment.
3. Specification as provided by the manufacturer
4. For sample, price, delivery, and availability Pl contact Mr. Varun – 9004365926
Mr. Nilesh – 9920494214, Office -91 22 28077450, 91-22 28017099