

Ref: PetEx.Spec.31

NAVJYOTI DEODOURISED KEROSENE SPECIFICATIONS

SR.NO.	PARAMETERS	TEST METHOD	UOM	SPECIFICATION	RESULTS
1.	SAYBOLT COLOUR	ASTM D156	SAYBOLT COLOUR	29 Min	29
2.	SPECIFIC GRAVITY @ 15.56°/15.56°C	ASTM D4052	NA	0.76 to 0.78	0.7684
3.	C13 PF AND LIGHTERS	UOP 688	wt %	15.0 Max	2.8
4.	C14 PF	UOP 688	wt %	52.0 Min	82.5
5.	>C14 PF	UOP 688	wt %	32.0 Max	14.6
6.	C15 PF	UOP 688	wt %	-	12.8
7.	C16 PF	UOP 688	wt %	-	1.6
8.	C17 PF	UOP 688	wt %	-	0.2
9.	SULPHUR		Wt. ppm	-	0.3
10.	BR. INDEX	ASTM D2710	Mg Br/100gm	15.0 Max	5.9
11.	IBP	245	-	245	245
12.	FBP	270	-	270	270

1. The photocopies of following license is required: GST Certificate
2. The price is subject to change. Pl confirm before payment.
3. Specification as provided by the manufacturer
4. For sample, price, delivery, and availability Pl contact Mr. Nilesh – 9920494214,
Mr. Varun – 9004365926, Office -91 22 28077450, 91-22 28017099