

Ref: PetEx.Spec.44

SPECIFICATIONS PLASTIC PYROLYSIS OIL

Sr.no	Parameters	Results	Test Result
1.	Appearance	Clear & Dark Yellow	
2.	Kinematic Viscosity @ 40°C , cSt	7.09	IS 448 (P25)1976
3.	Density @15.0°C, g/ml	0.78 – 0.79	IS 4730 - 1994
4.	Ash Content	0.004%	IS 448 (P-126)1998
5.	Gross Calorific, cal/gm	12087	IS 448 (P-7) 2004
6.	Flash Point , PMCC, °C	10°C	IS 448 (P-69)
7.	Sediments	0.059%	IS 1448 (Part 30)
9	Pour point, °C	-10	IS 1448 (P – 10)
10	Sulphur %	0.13	IS 448 (P-33) 1991
11.	Water content (By distillation) %	0.03	IS 2362 - 1993
12.	Acidity Inorganic mgKOH /gm	0.28	IS 1448 (P-2) - 2007

1. The price is subject to change. Pl confirm before payment.
2. Specification as provided by the manufacturer
3. The buyer should have Class B PESO Licence in addition to GST licence.
4. For sample, price, delivery, and availability Pl contact

Mr. Nilesh – 99204 94214, Mr. Varun – 9004365926, Office -91 22 28077450, 91-22 28017099