

Ref: PetEx.Spec.17A

## SPECIFICATION LIGHT DIESEL OIL (LDO) - HPCL

Sr.no	Parameters	Test Method	Units	Result Value
1.	Appearance	Visual	-	Dark
2.	Density 15°C - Top	IS 1448 P: 16	Kg/m <sup>3</sup>	887.5
3.	Density 15°C - Middle	IS 1448 P: 16	Kg/m <sup>3</sup>	887.5
4.	Density 15°C - Bottom	IS 1448 P: 16	Kg/m <sup>3</sup>	888.9
5.	Density 15°C	IS 1448 P: 16	Kg/m <sup>3</sup>	888.2
6.	Kinematic Viscosity @ 40°C	IS 1448 P: 25	cSt	5.145
7.	Flash Point - Pmcc	IS 1448 P: 21	°C	80
8.	Water Content	IS 1448 P: 40	% Vol	.100
9.	Sulphur Total	ASTM D 4294	% Mass	1.37
10.	Pour Point Summer	IS 1448 P: 10	°C	15

1. The photocopies of following licenses are required:  
GST Certificate, Explosive License for B class storage.
2. The price is subject to change. Pl confirm before payment.
3. Specification as provided by the manufacturer
4. For sample, price, delivery, and availability Pl contact Mr. Nilesh – 9920494214,  
Mr. Varun – 9004365926, Office -91 22 28077450, 91-22 28017099