

SPECIFICATIONS
“MIXED HYDROCARBON OIL (MHO)”

Sr. No.	Parameters	Test Method	Unit	Result
1.	Appearance		Visual	Water White
2.	Density @ 15°C	ASTM D 1298 -12BR17	Kg/l	0.8156
3.	Flash Point	ASTM D 93a-20	°C	56
4.	Viscosity @40°C	ASTM D 445-21e1	cSt	2.79
5.	DISTILLATION			
	IBP	ASTM D 86	°C	164
	10%	ASTM D 86	°C	200
	20%	ASTM D 86	°C	218
	30%	ASTM D 86	°C	240
	40%	ASTM D 86	°C	258
	50%	ASTM D 86	°C	273
	80%	ASTM D 86	°C	323
	90%	ASTM D 86	°C	347
	95%	ASTM D 86	°C	358
	FBP @ 98%	ASTM D 86	°C	382

1. The photocopies of following licenses are required: GST Licence, Explosive Class B storage licence.
2. The price is subject to change. Pl confirm before payment.
3. Specification as provided by the manufacturer
4. For sample, price, delivery, and availability Pl contact Mr. Varun – 9004365926
Mr. Nilesh – 9920494214, Office -91 22 28077450, 91-22 28017099