

Ref: PetEx.Spec.45

SPECIFICATIONS LSHS (HPCL)

Sr.no	Parameters	Test Method	Units	Result Value
1.	Density 15°C	IS 1448 P: 16	Kg/m3	943.4
2.	Density 15°C, TOP	IS 1448 P: 16	Kg/m3	943.3
3.	Density 15°C, MIDDLE	IS 1448 P: 16	Kg/m3	943.3
4.	Density 15°C, BOTTOM	IS 1448 P: 16	Kg/m3	944.0
5.	Kinematic Viscosity @ 100°C	IS 1448 P: 25 SEC 1	cSt	18.85
6.	Flash Point - Pmcc	IS 1448 P: 21	°C	98
7.	Water Content	IS 1448 P: 40	% Vol	0.25
8.	Sulphur Total	ASTM D 4294	% Mass	0.819
9.	Pour Point Summer	IS 1448 P:10 SEC 2	°C	0
10.	Gross Calorific Value	IS 1448 P:7	Cal/g	10430
11.	Sediment	IS 1448 P:30	% m/m	0.10
12.	Ash	IS 1448 P:4 SEC 1	% m/m	0.0550

1. The photocopies of following licenses are required: GST Certificate
2. The price is subject to change. Pl confirm before payment.
3. Specification as provided by the manufacturer
4. For sample, price, delivery, and availability Pl contact Mr. Varun – 9004365926, Office -91 22 28077450, 91-22 28017099